



Order No | B01060-00

Product Group 1000

Fire Control Panel "Solution F1-18"
Standard configuration for 2-18 loops and
max. 2.286 detectors / modules with
power supply 6,7 A / 24 V included

Modular, intelligent and ultra modern Fire Control Panel for
analogue addressable detectors and conventional detectors.
Prepared for 2 to 18 loops and / or 8 to 72 conventional zones.
Supports Hochiki ESP and CDX detectors as well as Apollo Orbis,
XP95 and Discovery.

DESCRIPTION :

- Panel can control up to 2.286 detectors / modules
- Power supply 24 V / 6,7 A included
- Slots for max. 9 loop cards and / or conventional detector cards
- max. of 1.024 zones can be organized
- Event memory log for 10.000 messages
- USB host interface e.g. for USB stick for export of panel data
- Metal rack for additional mounting area inside the panel (for system components)
- Interface for TFT display
- Slot for SD card to extend data memory Please order housing separate.

TECHNICAL SPECIFICATIONS :

Mains AC	230 V AC, 50/60 Hz
Operating voltage	24 V DC
Quiescent current	90 mA
Loops / Spurs	2 - 18 / 8 - 72
Power supply	6,7 A / 24 V
Batteries	max. 65 Ah / 24 V
IP rate	IP40
Weight	ca. 19,5 kg with housing B1
Dimensions	see housings

CERTIFICATIONS :

VdS approval : G 205 024
VdS System approval : S 205 024
EC-certificate : 0786-CPD-20907